



EasyConnect® 240-2

For ease of use and superior handling ...

The EasyConnect 240-2 creates a fast and easy way to connect and disconnect your instrument from a standard 3½"-8 mount. No more spinning of your instrument to thread it on or off its mount. The EasyConnect has a unique clamping system that allows easy connection to and separation from a standard mount through the use of a quick-action locking lever. The 240-2 includes an anti tipping feature to protect the instrument from falling off the stand. The EasyConnect attaches to any stand or other accessory having a 3½"-8 external thread.

A hole is located in the center of the base, for plummet shots when using optical transits and hollow stands.

Extensions mounted above the EasyConnect are not recommended.

You may also wish to look at our other stand accessories.



Components also available separately...

Part number	Description
19056	3½"-8 threaded ring only
19058	Base assembly without ring

Left: EasyConnect shown with mount removed.

Specifications

Diameter (housing): 4" (102mm)

Effective height*: 2.4" (60 mm)

Material: Stainless Steel and Anodized Aluminum Approximate weight: 3.6 lbs. (1.6 kg)

* Effective height is the distance from the lower interface surface to the upper interface surface, i.e., the additional elevation of an instrument when the 240-2 is inserted below it.

May be used with...

- Fits on any product having an external 3½"-8 thread.
- Accepts any product having an internal 3½"-8 thread.

Brunson Instrument Company • 8000 E. 23rd Street • Kansas City, MO • 64129 • USA
Tel: 816-483-3187 • Toll free: 877-MEASURE • Sales@brunson.us • www.brunson.us